

晶体谐振器 Crystal Resonator: KX502 KX602 KX702 KX802

Feature 特征

- Compact and ultra-thin profile for space-constrained devices 小尺寸，超薄设计，适用于空间受限设备
- Ceramic package ensures mechanical strength and thermal stability 陶瓷封装具有优良的机械强度和热稳定性
- Glass hermetic sealing provide excellent moisture resistance and long-term reliability 玻璃气密封装，防潮和可靠性好



General Specifications 规格参考

PARAMETER	性能参数	KX502	KX602	KX702	KX802
Package Size	尺寸	5.0 x 3.2 mm	6.0 x 3.5 mm	7.0 x 5.0 mm	8.0 x 4.5 mm
Frequency Range	频率范围	8~125MHz	8~40MHz	7.37~70MHz	4~70MHz
Oscillation Mode	振荡方式	基频/泛音			
Frequency Tolerance (25°C±3°C)	调整频差	±10ppm, ±20ppm, ±30ppm (max)			
Load Capacitance	负载电容	Series or Parallel (8~32pF)			
Frequency Stability	温度频差	见下表			
Operating Temperature Range	温度范围	见下表			
Equivalent Series Resistance	谐振电阻	50~100 Ω	50~100 Ω	50~100 Ω	300 Ω Max
Drive Level	激励电平	10μW typical, 100μW max			
Shunt Capacitance	静电容	3.5pF max	7pF max		
Insulation Resistance	绝缘电阻	500MΩ min			
Storage Temperature Range	储存温度范围	-55°C to +125°C			
Aging Per Year	年化率	±3ppm/year max			

Frequency Stability 温度频差 VS Operating Temperature Range 温度范围						
Temp. Code	Temp.\ppm	±10	±20	±30	±50	±100
B	-20~70°C	○	○	○	○	○
C	-40~85°C		○	○	○	○
D	-55~85°C				○	○
E	-55~105°C				○	○
F	-55~125°C					○

NOTE: Please consult for other specifications 若有其它规格需求请告知

■ Outline Dimensions (Unit: mm) 外形尺寸

KX502	
KX602	
KX702	
KX802	

■ Part Number Guide 产品编号

<u>KX502</u>	-	<u>24.576</u>	-	<u>F</u>	-	<u>20</u>	-	<u>C</u>	-	<u>30</u>	-	<u>30</u>	-	<u>NS</u>
↓		↓		↓		↓		↓		↓		↓		↓
型号	-	标称频率	-	振荡方式	-	负载	-	工作温度	-	调整频差	-	温度频差	-	特殊要求

‘KX’: 产品系列
‘50’: 封装尺寸
SMD5.0x3.2mm
(MHz 频率产品
后加两位数字)
‘2’: 引脚数

(In MHz)


F-基频
T-泛音

B: -20~+70°C
C: -40~+85°C
D: -55~+85°C
E: -55~+105°C
F: -55~+125°C

10 = ±10ppm
20 = ±20ppm
30 = ±30ppm

10 = ±10ppm
20 = ±20ppm
30 = ±30ppm
50 = ±50ppm
100 = ±100ppm

■ Reflow Profile 回流焊



Temperature Min Preheat	最低预热温度	T _{smin}	150°C
Temperature Max preheat	最高预热温度	T _{smax}	200°C
Time (T _{smin} to T _{smax})	时间差	T _s	60~120 sec
Temperature	温度	T _L	217°C
Peak Temperature	最高温	T _p	260 °C
Ramp-up Rate	升温速度	R _{up}	3°C/sec max
Ramp-down Rate	降温速度	R _{down}	6°C/sec max
Time within 5°C of Peak Temperature	最高温度停留时间	t _p	30 sec
Time t[25°C] to peak temperature	25度到最高温度时间	t[25°C] to peak	480 sec
Time	时间	t _L	60~150 sec

■ Revision 版本

版本 Rev.	修改页 Revise Page	修改内容 Revise Contents	日期 Date	修改人 Reviser
0	N/A	Initial issue	2020.09.27	JZ
1	1,2	Add new product	2025.06.23	JZ
1.1	1	Specs update	2025.12.04	JZ