

压控振荡器 Voltage Controlled Crystal Oscillator: KV32T KV50T KV70T

Feature 特征

- VCXO allow for precise frequency tuning over typical range $\pm 80\sim 200\text{ppm}$ by adjusting the voltage on the control (Vc) pin 压控晶振可以通过调节控制引脚上的电压进行微调, 频率微调范围为 $\pm 80\sim \pm 200\text{ppm}$
- CMOS output with wide frequency range, up to 245MHz 频率范围广, 最高 245MHz
- Low phase jitter 0.6ps RMS 低相位抖动, 满足高速数字系统要求
- Ideal for high performance communication, video, and industrial timing systems 适用于高性能通信, 视频处理, 工业控制等
- Available in compact packages such as 3225, 5032, 7050 可选多种尺寸



General Specifications 规格参考




| PARAMETER | 性能参数 | KV32T KV50T KV70T | |
|-----------------------------|---------|--|----------------------|
| Frequency Range | 频率范围 | 10.0 ~ 245.0MHz | |
| Supply Voltage | 供给电压 | +2.5V ($\pm 10\%$) | +3.3V ($\pm 10\%$) |
| Center Control Voltage | 中心控制电压 | 1.25Vdc (0.25V~2.25V) | 1.65Vdc (0.3V~3.0V) |
| Output Logic | 输出波形 | CMOS | |
| Output Load | 输出负载 | 15pF | |
| Frequency Tolerance | 调整频差 | $\pm 20\text{ppm}$ | |
| Current Consumption | 工作电流 | 40mA max. | |
| Output Logic High "1" | 输出电平 高 | 0.9Vdd min. | |
| Output Logic Low "0" | 输出电平 低 | 0.1Vdd max. | |
| Frequency Pulling Range | 压控范围 | $\pm 80\sim \pm 200\text{ppm}$ | |
| Integrated Phase Jitter | 抖动 | 0.6ps max. (12KHz~20MHz) | |
| Input Impedance | 输入电阻 | 1M Ω typical | |
| Rise & Fall Time | 上升下降时间 | 10ns max. | |
| Start-up Time | 起振时间 | 10ms max. | |
| Output Enable/Disable Time | 启动/禁用时间 | Enable: 200ns max. Disable: 50ns max. | |
| Linearity | 非线性误差 | $\pm 5\%$ typical, $\pm 10\%$ max. | |
| Duty Cycle | 占空比 | 45~55% (f \leq 40MHz); 40~60% (f > 40MHz) | |
| Modulation Bandwidth (-3dB) | 调制宽带 | 10KHz min. | |
| Aging Per Year | 年化率 | $\pm 3\text{ppm} \sim \pm 5\text{ppm}/\text{year}$ | |
| Storage Temperature Range | 储存温度范围 | -55 $^{\circ}\text{C} \sim +125^{\circ}\text{C}$ | |

Frequency Stability 温度频差 VS Operating Temperature Range 温度范围

| Temp. Code | Temp. ppm | ± 20 | ± 25 | ± 30 | ± 50 | ± 100 |
|------------|----------------------------|----------|----------|----------|----------|-----------|
| B | -20~70 $^{\circ}\text{C}$ | o | o | o | o | o |
| C | -40~85 $^{\circ}\text{C}$ | | o | o | o | o |
| E | -40~105 $^{\circ}\text{C}$ | | | | o | o |
| F | -55~125 $^{\circ}\text{C}$ | | | | | o |

NOTE: Please consult for other specifications 若有其它规格需求请告知

Outline Dimensions (Unit: mm) 外形尺寸

| <p>KV32T</p> |  | | | | | | | | | | | | | | |
|---------------------|---|-----|------------|----|-----------------|----|-----------|----|--------|----|--|----|---|----|----------------|
| <p>KV50T</p> |  | | | | | | | | | | | | | | |
| <p>KV70T</p> |  | | | | | | | | | | | | | | |
| | <table border="1" data-bbox="649 1218 1112 1470"> <thead> <tr> <th>Pin</th> <th>Connection</th> </tr> </thead> <tbody> <tr> <td>#1</td> <td>Control Voltage</td> </tr> <tr> <td>#2</td> <td>Tri-State</td> </tr> <tr> <td>#3</td> <td>Ground</td> </tr> <tr> <td>#4</td> <td>CMOS: Output; PECL or LVDS: Differential</td> </tr> <tr> <td>#5</td> <td>CMOS: N.C.; PECL or LVDS: Complementary</td> </tr> <tr> <td>#6</td> <td>Supply Voltage</td> </tr> </tbody> </table> | Pin | Connection | #1 | Control Voltage | #2 | Tri-State | #3 | Ground | #4 | CMOS: Output; PECL or LVDS: Differential | #5 | CMOS: N.C.; PECL or LVDS: Complementary | #6 | Supply Voltage |
| Pin | Connection | | | | | | | | | | | | | | |
| #1 | Control Voltage | | | | | | | | | | | | | | |
| #2 | Tri-State | | | | | | | | | | | | | | |
| #3 | Ground | | | | | | | | | | | | | | |
| #4 | CMOS: Output; PECL or LVDS: Differential | | | | | | | | | | | | | | |
| #5 | CMOS: N.C.; PECL or LVDS: Complementary | | | | | | | | | | | | | | |
| #6 | Supply Voltage | | | | | | | | | | | | | | |

Part Number Guide 产品编号

| | | | | | | | | | | | | |
|--------------|---|---------------|---|------------|---|-----------|---|----------|---|-----------|---|-----------|
| KV32T | - | 27.000 | - | 100 | - | 33 | - | C | - | 30 | - | NS |
| ↓ | | ↓ | | ↓ | | ↓ | | ↓ | | ↓ | | ↓ |
| 型号 | - | 标称频率 | - | 压控范围 | - | 工作电压 | - | 工作温度 | - | 温度频差 | - | 特殊要求 |

‘KV’: 压控系列
 ‘32’: 封装尺寸
 3.2x2.5mm
 ‘T’: 输出波形
 CMOS

(In MHz)

80=±80ppm
 100=±100ppm
 150=±150ppm
 200=±200ppm


25=2.5V
 33=3.3V

B: -20~+70°C
 C: -40~+85°C
 E: -40~+105°C
 F: -55~+125°C

10 = ±10ppm
 20 = ±20ppm
 30 = ±30ppm
 50 = ±50ppm
 100 = ±100ppm

‘NS’:特殊要求

■ Reflow Profile 回流焊



| | | | |
|--|------------|-------------------------------|-------------|
| Temperature Min Preheat | 最低预热温度 | T_{smin} | 150°C |
| Temperature Max preheat | 最高预热温度 | T_{smax} | 200°C |
| Time (T_{smin} to T_{smax}) | 时间差 | T_s | 60~120 sec |
| Temperature | 温度 | T_L | 217°C |
| Peak Temperature | 最高温 | T_p | 260 °C |
| Ramp-up Rate | 升温速度 | R_{up} | 3°C/sec max |
| Ramp-down Rate | 降温速度 | R_{down} | 6°C/sec max |
| Time within 5°C of Peak Temperature | 最高温度停留时间 | t_p | 30 sec |
| Time $t[25^\circ\text{C}]$ to peak temperature | 25度到最高温度时间 | $t[25^\circ\text{C}]$ to peak | 480 sec |
| Time | 时间 | t_L | 60~150 sec |